

KALAHARI

A low VOC, water-based textured paint formulated with acrylic resin and fine glass beads. Tribe Kalahari finish gives a fine grained look to the surface.



APPLY WITH

- Brush "6"
- Brush "4"
- Roller



RECOMMENDED FOR

Interior surfaces only. Not suitable for use on substrates where there is contact with water, such as bathrooms, kitchen sinks and damp walls.

TRIBE

SURFACE PREPARATION

- Surface must be dry and moisture content of surface should not be more than 10% when measured with a moisture meter.
- Surfaces must be free of dirt, dust, grease, loose particles and flaking paint.
- Surface must be smooth and even to avoid see-through of surface and other imperfections should be filled with suitable wall primer.
- Sanding is recommended for new substrates to remove dirt and cement flashes.

APPLICATION

- It is highly recommended that Tribe Kalahari be applied by a trained applicator to achieve desired finish and effect.
- Apply 1 coat of Tribe Fine Primer tinted to the chosen Tribe Kalahari colour, with a roller to obtain a uniform surface coverage
- Allow Tribe Fine Primer to dry completely before applying the second coat.
- Recoat Tribe Fine Primer with roller and allow complete drying before applying Tribe Kalahari. Drying time of Tribe Fine Primer shall depend on weather conditions. Ideally 4 hours would be sufficient.
- 2 coats of Tribe Kalahari at the spread rate of 5m²/liter are recommended to achieve desired finish and effect.
- Apply first coat of Tribe Kalahari with roller and create crisscross patterns using a clean 6-inch brush. Allow to dry for 4-6 hours.
- Recoat Tribe Kalahari using same technique as above and allow to dry overnight.

PRECAUTIONS

- The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.
- It is recommended that the surface where products are being applied is not dry during application process, to avoid marks caused by the application tools being used.
- Touch ups are not recommended, apply from corner to corner, or from a natural cut off point to another.
- Do not apply thick layers of Tribe Kalahari as it will take too long to dry.

IMPORTANT TO NOTE

- Considering the nature of this product, its colour can vary slightly from batch to batch.
- Due to the application technique, the texture may also vary.

DISCLAIMER

THIS GUIDE IS BASED ON EXTENSIVE LAB TESTS AND FIELD USE. HOWEVER, IF USED UNDER UNSPECIFIED CONDITIONS AND IF APPLICATION INSTRUCTIONS ARE NOT FOLLOWED CORRECTLY, THE PERFORMANCE OF THE PRODUCT MAY DIFFER.

FOR ANY FURTHER INFORMATION PLEASE REFER TO THE TECHNICAL DATA SHEET OR CONTACT OUR TECHNICAL DEPARTMENT.