

PALETTE OF AFRICA

A low VOC, high quality, water-based paint suitable for walls and ceilings on interior and exterior surfaces. It dries to give a matt finish.



APPLY WITH

- Brush "6"
- Brush "4"
- Roller



RECOMMENDED FOR

Recommended for interior and exterior surfaces.

TRIBE

SURFACE PREPARATION

- Surface must be dry and moisture content of surface should not be more than 10% when measured with a moisture meter.
- Surfaces must be free of dirt, dust, grease, loose particles and flaking paint.
- Surface must be smooth and even to avoid see-through of surface and other imperfections should be filled with suitable wall primer.
- Sanding is recommended for new substrates to remove dirt and cement flashes.

APPLICATION

- Apply 1 coat of Tribe Palette of Africa at the spread rate of 7-8 m²/liter by brush or roller. 5% and 10% dilution with water is recommended for brush and roller application respectively.
- Allow to dry for 3-4 hours depending on the weather and substrate temperature.
- Subsequent coats do not require thinning.
- Recoat Tribe Palette of Africa using same technique as first coat and allow complete drying.
- 2 coats of Tribe Palette of Africa are normally sufficient to give good obliteration.

PRECAUTIONS

- The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.
- Do not apply to very cold surfaces, or to Fletton bricks.
- Do not over-dilute the product.
- It is recommended that the surface where products are being applied is not dry during application process, to avoid marks caused by the application tools being used.

DISCLAIMER

THIS GUIDE IS BASED ON EXTENSIVE LAB TESTS AND FIELD USE. HOWEVER, IF USED UNDER UNSPECIFIED CONDITIONS AND IF APPLICATION INSTRUCTIONS ARE NOT FOLLOWED CORRECTLY, THE PERFORMANCE OF THE PRODUCT MAY DIFFER.

FOR ANY FURTHER INFORMATION PLEASE REFER TO THE TECHNICAL DATA SHEET OR CONTACT OUR TECHNICAL DEPARTMENT.