

ZAMBEZI PASTE

A low VOC, premium quality water based product with a metallic luster finish.



APPLY WITH

- Steel trowel
- Brush "6"
- Roller



RECOMMENDED FOR

Interior surfaces only. Not suitable for use on substrates where there is contact with water such as bathtubs, kitchen sinks and damp walls.

TRIBE

SURFACE PREPARATION

- Surface must be dry and moisture content of surface should not be more than 10% when measured with a moisture meter.
- Surfaces must be free of dirt, dust, grease, loose particles and flaking paint.
- Surface must be smooth and even to avoid see-through of surface and other imperfections should be filled with suitable wall primer.
- Sanding is recommended for new substrates to remove dirt and cement flashes.

APPLICATION

- It is highly recommended that Tribe Zambezi Paste be applied by a skilled applicator to achieve desired finish and effect.
- Apply 1 coat of Tribe Palette of Africa tinted to the selected Tribe Zambezi Paste colour with a roller to obtain a uniform surface coverage.
- Allow Tribe Palette of Africa to dry completely before applying the second coat.
- Recoat Tribe Palette of Africa with roller and allow complete drying before applying Tribe Zambezi Paste.
- Drying time of Tribe Palette of Africa shall depend on weather conditions. Ideally 4 hours would be sufficient.
- 2 coats of Tribe Zambezi Paste at the spread rate of 3m²/liter are recommended for a good finish.
- Apply first coat of Tribe Zambezi Paste with roller and create texture by applying the product in circular motions using a clean humid steel trowel and water.
- First coat will require a minimum of 4 hours to dry.
- Recoat Tribe Zambezi Paste using same technique as above and allow to dry overnight.

PRECAUTIONS

- The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.
- It is recommended that the surface where products are being applied is not dry during application process, to avoid marks caused by the application tools being used.
- Touch ups are not recommended, apply from corner to corner, or from a natural cut off point to another.

IMPORTANT TO NOTE

- Considering the nature of this product, its colour can vary slightly from batch to batch.
- Due to the application technique, the texture may also vary.

DISCLAIMER

THIS GUIDE IS BASED ON EXTENSIVE LAB TESTS AND FIELD USE. HOWEVER, IF USED UNDER UNSPECIFIED CONDITIONS AND IF APPLICATION INSTRUCTIONS ARE NOT FOLLOWED CORRECTLY, THE PERFORMANCE OF THE PRODUCT MAY DIFFER.

FOR ANY FURTHER INFORMATION PLEASE REFER TO THE TECHNICAL DATA SHEET OR CONTACT OUR TECHNICAL DEPARTMENT.