

TRIBE

TECHNICAL DATA SHEET

PALETTE OF AFRICA

DESCRIPTION

TRIBE PALETTE OF AFRICA is a low VOC, high quality, water-based paint suitable for walls and ceilings on interior and exterior surfaces. It dries to give a matt finish.

TYPE/COMPOSITION

An emulsion based paint formulated with a high durability acrylic resin and incorporating the highest quality pigments specially selected for their performance.

SUBSTRATE RECOMMENDATION

Recommended for interior and exterior surfaces.

SURFACE PREPARATION

- Surface must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter.
- Surfaces must be free of dirt, dust, grease, loose particles and flaking paint.
- Surface must be smooth and even to avoid see-through of surface and other imperfections should be filled with suitable wall primer.
- Sanding is recommended for new substrates to remove dirt and cement flashes.

APPLICATION

- 2 coats of Tribe Palette of Africa are normally sufficient to give good obliteration
- Apply the 1st coat of Tribe Palette of Africa at the spread rate of 7-8 m²/liter by brush or roller. Dilute with water at 5% for brush application and 10% for roller application
- Allow to dry for 3-4 hours depending on the weather and substrate temperature.
- Subsequent coats do not require thinning.
- Recoat Tribe Palette of Africa and allow complete drying.

TRIBE

TECHNICAL DATA SHEET

PHYSICAL DATA

Viscosity	110-120 KU
Specific Gravity	1.13-1.23
pH	8.5-9
Weight Solids Content	50% (± 5%)
Volume Solids Content	40% (± 5%)
Spread Rate	7-8m ² /liter
Application Temperatures	> 10° C < 35 ° C
Storage Temperatures	> 5° C < 35 ° C
Shelf Life of unopened containers	12 months
Vehicle Type	Pure Acrylic
Cleaning Solvent	Water

SHADES

Refer to Colour Card

PRECAUTIONS

- The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.
- Do not apply to very cold surfaces, or to Fletton bricks.
- Do not over-dilute the product.
- It is recommended that the surface where products are being applied is not dry during application process, to avoid marks caused by the application tools being used.

THINNING

Recommended for the 1st coat only; 5% and 10% dilution with water is recommended for brush and roller application respectively. Subsequent coats do not require thinning.

CLEANING

Wash equipment with clean water immediately after use

PACKAGING

Available in 1 & 5 liters

STORAGE

Store in a cool, dry and well-ventilated place. Storage temperature should be > 5° C < 35° C

TRIBE

TECHNICAL DATA SHEET

HEALTH & SAFETY

- Handle with Care.
- Avoid contact with skin and eyes
- If contact with skin occurs, wash well with soap and water.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Use in well-ventilated areas.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- If swallowed, seek medical advice immediately and show this container or label.
- Do not use empty paint containers for storing foodstuffs.

For further information, please contact our Technical Information Service.

Important to Note:

- Considering the nature of this product, its colour can vary slightly from batch to batch.
- This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container

Date: January 2014