

TRIBE Textured Acrylic Primer

DESCRIPTION

TRIBE Textured Acrylic Primer is a textured water based alkaline resistant plaster primer for use on a number of substrates prior to applying of TRIBE Rumsiki, TRIBE Giza and TRIBE Etosha, textured coatings. It has excellent obliteration properties to ensure that the substrate is evenly covered.

TRIBE Textured Acrylic Primer can be used for both interior and exterior on properly prepared surfaces such as plaster, cement, bricks, composite boards etc.

CHARACTERISTICS

- Eco-friendly
- Free of MEG, APEO & AMMONIA
- Free of Crystalline Silica therefore no concerns about Silicosis
- Low VOC product
- Excellent application and adhesion properties
- Effective for hiding minor surface imperfections
- Water based, ready to use, low odour and quick drying
- It has a low odour and a breakthrough additive to prevent fungal and algae growth
- The actives within have improved resistance to Alkali, UV and leaching, ensuring better long-term stability and efficiency
- Excellent adhesion and penetration properties
- Water resistant but still allows the substrate to breathe

SURFACE PREPARATION

- All surfaces must be properly prepared to ensure that they are sound, dry and clean.
- Surfaces must be free of dirt, dust, grease, loose particles and flaking paint.
- Surface must be smooth and even to avoid see-through of surface and other imperfections should be filled with suitable wall primer.
- Sanding is recommended for new substrates to remove dirt and cement flashes.

APPLICATION

- | | |
|----------|------------------|
| Method | Brush and Roller |
| Thinning | Ready to use |
- Stir thoroughly and apply 1 even coat by brush and/or roller at the specified spread rate.
 - Ensure that the surface is properly obliterated.
 - Allow to dry before over-coating with the final finishing product.

PRODUCT INFORMATION

- | | | |
|----------------|--|-----------------|
| Binder Type | Pure Acrylic Binder | |
| Colour | White & Pastel | |
| Spreading Rate | 5 – 6 m ² / lt, Depends on the condition and porosity of the substrate and the application method being used. | |
| VOC | In compliance with world standards of <5g/litre for VOC | |
| Drying Time | Surface Dry | 1 hour at 25°C |
| | Hard Dry | 1 hour at 25°C |
| | Overcoating | 4 hours at 25°C |

TRIBE

TECHNICAL DATA SHEET

PRECAUTIONS	<ul style="list-style-type: none">• All spread rates are approximate and are dependent on substrate type and profile, tools used and loss factor due to weather conditions. Always ensure adequate drying times of the products are adhered to so as not to compromise the product performance. Hot, humid, cold or wet conditions will affect the drying time. The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.
PACKAGING - BASE	<ul style="list-style-type: none">• 5 and 20 Lt
STORAGE	<ul style="list-style-type: none">• Store unopened in a cool, dry and well-ventilated place for up to 6 to 8 months.
SAFETY, HEALTH & ENVIRONMENT INFORMATION	<ul style="list-style-type: none">• Handle with care• Ensure good ventilation during application.• In case of insufficient ventilation during painting, wear suitable respiratory equipment.• Avoid contact with skin and eyes.• If contact with skin occurs, wash well with soap and water.• In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.• Keep out of reach of children.• Do not use empty paint containers for storing foodstuffs.• Do not throw paint containers or contents in the waterways or environment.• Contains no added Lead / Mercury / Nickel / Cadmium.

For further information, kindly contact our Technical Information Service.

Note: This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container.