

TRIBE

TECHNICAL DATA SHEET

TRIBE TIMBUKTU

DESCRIPTION	TRIBE TIMBUKTU is a low VOC, acrylic water-based textured finish. It dries to give an attractive rustic look with a gritty textured finish.
TYPE/COMPOSITION	Emulsion paint based on highly durable polymeric medium and incorporating pigments with quartz.
SUBSTRATE RECOMMENDATION	Recommended for interior and exterior surfaces.
SURFACE PREPARATION	<ul style="list-style-type: none">• Surface must be dry and moisture content of surface should not be more than 10 % when measured with a moisture meter.• Surfaces must be free of dirt, dust, grease, loose particles and flaking paint.• Surface must be smooth and even to avoid see-through of surface and other imperfections should be filled with suitable wall primer.• Sanding is recommended for new substrates to remove dirt and cement flashes.
APPLICATION	<ul style="list-style-type: none">• It is highly recommended that TRIBE Timbuktu be applied by a trained applicator to achieve desired finish and effect.• Apply a 1st coat of a water-based acrylic paint tinted to the chosen TRIBE Timbuktu colour, with a roller to obtain a uniform surface coverage• Allow the water-based acrylic paint to dry completely before applying the second coat. Drying time of the water-based acrylic paint shall depend on weather conditions. Ideally ± 4 hours would be sufficient.• 2 coats of TRIBE Timbuktu at the spread rate of 2m²/liter are recommended to achieve desired finish and effect.• Apply a 1st coat of TRIBE Timbuktu with roller and immediately smooth the surface vertically using a block brush to achieve required grain design.• Allow to dry for 6-7 hours.• Recoat TRIBE Timbuktu using same technique as above and allow to dry overnight.

TRIBE

TECHNICAL DATA SHEET

PHYSICAL DATA

Viscosity	135-140 KU
Specific Gravity	1.48 (± 5%)
pH	8.5 – 9.5
Weight Solids Content	72 (± 5%)
Volume Solids Content	50 (± 5%)
Spread Rate	2m ² /liter
Application Temperatures	> 10° C < 35 ° C
Storage Temperatures	> 5° C < 35 ° C
Shelf Life of unopened containers	12 months
Vehicle Type	Pure Acrylic
Cleaning Solvent	Water

SHADES

Refer to Samples at Point of Sales

PRECAUTIONS

- The air temperature must not be below 10°C and not higher than 35°C. Humidity must not be below 10% and not higher than 85%.
- It is recommended that the surface where products are being applied is not dry during application process, to avoid marks caused by the application tools being used.
- Touch ups are not recommended, apply from corner to corner, or from a natural cut off point to another.
- Do not apply thick layers of **TRIBE Timbuktu** as it will take too long to dry.

THINNING

Not recommended

CLEANING

Wash equipment with clean water immediately after use

PACKAGING

Available in 1 & 5 liters

STORAGE

Store in a cool, dry and well-ventilated place. Storage temperature should be > 5° C < 35° C

TRIBE

TECHNICAL DATA SHEET

HEALTH & SAFETY

- Handle with Care.
- Avoid contact with skin and eyes
- If contact with skin occurs, wash well with soap and water.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Keep out of reach of children.
- Use in well-ventilated areas.
- In case of insufficient ventilation during painting, wear suitable respiratory equipment.
- If swallowed, seek medical advice immediately and show this container or label.
- Do not use empty paint containers for storing foodstuffs.

For further information, please contact our **Technical Information Service**.

Important to Note:

- Considering the nature of this product, its colour can vary slightly from batch to batch and the texture can vary too due to its application technique.
- This Technical Data Sheet is subject to change without prior notice.

DISCLAIMER

This data sheet is based on extensive lab tests and field use. However, if used under unspecified conditions, the performance of the product may differ. We can only guarantee the quality of the product as supplied in its original closed container

Date: 18th August 2022